



BELLOW & COMPENSATOR	MATERIAL***	BELLOWFLANGE (304) & TC (316 L)
----------------------	-------------	---------------------------------

A	B	C		D		EPDM*		VITON*		A ^{TC}	E	F	G	H	I	TK
		1	4	8	10	white	black**	white	black**							
100	135	•				•	•	◦	◦	100/4"	152.5	12	ø6.5 8x45°	35	119	ø137 8xM6
100	245	•				•	•	◦	◦	100/4"	152.5	12	ø6.5 8x45°	35	119	ø137 8xM6
100	135		•			•	•	◦	◦	100/4"	152.5	12	ø6.5 8x45°	35	119	ø137 8xM6
100	245		•			•	•	◦	◦	100/4"	152.5	12	ø6.5 8x45°	35	119	ø137 8xM6
100	60			◦		•	•	◦	◦	100/4"	152.5	12	ø6.5 8x45°	35	119	ø137 8xM6
150	135	•				•	•	◦	◦	150/6"	203.5	15	ø6.5 8x45°	35	167	ø186 8xM6
150	245	•				•	•	◦	◦	150/6"	203.5	15	ø6.5 8x45°	35	167	ø186 8xM6
150	135		•			•	•	◦	◦	150/6"	203.5	15	ø6.5 8x45°	35	167	ø186 8xM6
150	245		•			•	•	◦	◦	150/6"	203.5	15	ø6.5 8x45°	35	167	ø186 8xM6
150	60			•		•	•	◦	◦	150/6"	203.5	15	ø6.5 8x45°	35	167	ø186 8xM6
200	150	•				•	•	◦	◦	200/8"	254.5	15	ø6.5 8x45°	35	217.7	ø232 8xM6
200	283	•				•	•	◦	◦	200/8"	254.5	15	ø6.5 8x45°	35	217.7	ø232 8xM6
200	150		•			•	•	◦	◦	200/8"	254.5	15	ø6.5 8x45°	35	217.7	ø232 8xM6
200	283		•			•	•	◦	◦	200/8"	254.5	15	ø6.5 8x45°	35	217.7	ø232 8xM6
200	60			•		•	•	◦	◦	200/8"	254.5	15	ø6.5 8x45°	35	217.7	ø232 8xM6
250	150	•				•	•	◦	◦	250/10"	304.5	15	ø6.5 8x45°	40	268	ø287 8xM6
250	283	•				•	•	◦	◦	250/10"	304.5	15	ø6.5 8x45°	40	268	ø287 8xM6
250	150		•			•	•	◦	◦	250/10"	304.5	15	ø6.5 8x45°	40	268	ø287 8xM6
250	283		•			•	•	◦	◦	250/10"	304.5	15	ø6.5 8x45°	40	268	ø287 8xM6
250	60			•		•	•	◦	◦	250/10"	304.5	15	ø6.5 8x45°	40	268	ø287 8xM6
300	145		•			•	•	◦	◦	300/12"	361.5	18	ø8.5 8x45°	40	319	ø341 8xM8
300	275		•			•	•	◦	◦	300/12"	361.5	18	ø8.5 8x45°	40	319	ø341 8xM8
300	70			•		•	•	◦	◦	300/12"	361.5	18	ø8.5 8x45°	40	319	ø341 8xM8

* FDA Compliant	A ^{TC} DIN 32676/ BS 4825	X flange with threadhole
** conductive	• in stock	Y clearance hole
*** other materials on request	◦ manufactured to order	Z depending on customer requirement